RESIDENTIAL
CONTROL
VALVES



Performa™ Control Valves

263 and 268 Configurations

Logix™ Series

740 Time Clock

- Simple, economic electronic time clock (chronometric)
- 7- or 99-day regeneration setting
- High efficiency regeneration sequence
- 12-volt operation
- Filter or conditioner setting in one control
- Operates 255, 263, 268 with one controller

742 Time Clock

Same features as the 740 Time Clock, plus:

- Fully programmable cycle times
-

Pentair Water

Performa™ Control Valves

263 and 268 Configurations

Electrical

Controller Operating Voltage	12 Volt – AC (Requires use of Pentair Water®-supplied transformer)
Input Supply Frequency	50 or 60 Hz (Controller configuration dependent)
Motor Input Voltage	12 Volt – AC
Controller System Power Consumption	3 Watts average

Transformer – All Controllers

All Controllers require the use of a Pentair Water-supplied transformer.

Transformer Output Voltage	12 Volt – AC 400mA	
Transformer Input Options	115 Volt – AC 50/60 Hz; 230 Volt – AC 50/60 Hz; 100 Volt – AC 50/60 Hz	
Transformer Plug Options	Indoor North American Plug	Taiwan/Korea Plug
	Outdoor North American (UL Listed for outdoor use)	Australian Plug
		United Kingdom Plug
	Japanese Plug	Mainland Europe Plug

Additional transformers may be available – call for more information.

SERVICE FLO

Pentair Wat

20580 Enterprise Avenue
Brookfield, WI 53045
Tel: 262.784.4490
Fax: 262.784.7794

5730 North Glen Park Road
Milwaukee, WI 53209
Tel: 262.238.4400
Fax: 262.238.4402

Customer Care: 800.279.9404 www.pentairwatertreatment.com

©2010 Pentair Residential Filtration, LLC
1223489 Rev D FE10