



AUTOLOG 363 AUTOMATIC FILTER VALVE

COMPACT, LOW-PROFILE SOLUTION FOR A BROAD RANGE OF FILTRATION APPLICATIONS

FEATURES / BENEFITS

Time-tested Duraflow flapper provides frictionless sealing for longer service life

Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant

Optical sensor for precision cycle positioning

Fully adjustable 3 cycle control for efficient and reliable water treatment system

Continuous service flow rate of 21 GPM with a backwash of 19 GPM

Backwash capability accommodates filter up to 36" in diameter

Super capacitor for keeping time of day during power outage



ELECTRICAL

ANSIFORMATION

AL E SPECIFICATION

Valve Body

Valve Color

Operating Pressure

Water Temperature

Ambient Temperature

PERFORMANCE

Drain Line Flow Control

4-20 gpm

Full Flow Body

Service: 21 gpm
Backwash: 19 gpm
Fast Rinse: 5 gpm

AL E CONNECTION

Tank Thread

2.5"

Inlet/Outlet

1" NPT or 1" BSP

Inlet/Outlet
(center to center)

4"

Drain Location

0.75" below inlet/outlet

DIMENSION

Width

7.8"

Height

3.35"

Riser Tube Dia.

1.05"

Riser Height

Flush +/- 0.5"



FILE INFORMATION & COE

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | F: 262.238.4404 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404

